



A Healthier & Better Choice!



LSM - 939 - HWC (HOT/WARM/COLD Water)

Special Features & Specifications:

- Double secure prevents from overheat or dry-heat (by sensor and thermostat).
- Double secure against water overflow (by sensor and floating valve)
- Automatic control for purified water refill.
- Chilling system by compressor with R-134a refrigerant.
- One piece blow molded high-density polyethylene plastic.
- ABS plastic base - shock absorbing and will never rust.

Filters:

- F1 - Sediment Filter
- F2 - Activated Carbon Filter
- F4 - Post Activated Carbon Filter

Dimension: W38 x D40 x H105 cm

Net Weight (kg): 19 kg

Chilling capacity:

- 20L/hour, chilled water under 10 degree C.

Heating capacity:

- 10L/hour, able to produce 100 degree C with re-boil function..
- Hot water temperature at 85 degree C to 90 degree C.
- Hot water tap with safety device.

Capacity of each tank :

- Individual hot water tank: 3L.
- Individual chilled water tank: 4L.
- Room water tank: 10L

Power Consumption :

- Hot water - 700W
- Chilled water - 100W



Comply with ARI standards and are listed by UL. Certified by CSA and VDE. Conform to European Standards. All parts that come in contact with water are made from FDA approved material.